



Protective-decorative coating
Washed gravel, fraction 2-5 mm
Drainage membrane with geotextile
Extruded polystyrene
TECHNONICOL CARBON PROF 300
Heat-treated needle-punched
geotextile 300 g/sq.m
Underlay waterproofing bitumen membrane
Underlay waterproofing bitumen membrane
Bitumen primer TECHNOMICOL No. 01
Reinforced sand-cement screed
Sloping of expanded clay gravel
Reinforced concrete foundation

- | | |
|--|--|
| ① Strengthening layer - Underlay bitumen membrane | ⑥ Bottom layer of waterproofing system on vertical surface - Underlay bitumen membrane |
| ② Heat-treated needle-punched geotextile 150 g/sq.m | ⑦ Fastening element |
| ③ Washed gravel | ⑧ Galvanized steel flashing |
| ④ Protective galvanized steel flashing | ⑨ Antiseptic treated timber |
| ⑤ Top layer of waterproofing system on vertical surface - Cap sheet bitumen membrane | ⑩ Roof edge railing |

				TERRACE WITH DRAINAGE	DESIGN	APPROVED
				JUNCTION TO PARAPET	SCALE	DATE
REV.	DATE	DESCRIPTION	CHECKED		DWG No.	REV.