


DECLARATION OF PERFORMANCE

No. MW/012R/CE/2018_06

1. **TECHNOVENT STANDARD.** MW-EN 13162-T4- DS(70,-) DS(23,90)-CS(10)10-TR5-PL(5)100-WS-WL(P)-MU1
RtF:A1
2. Intended use: Thermal insulation boards for building
3. Manufacturer:
Limited Liability Company "Heat-Insulating Plant "TECHNO"
Having its seat in: LLC "Zavod TECHNO", Ryazan, Vostochnij Promuzel, building 21/58
ORIGIN: Russian Federation
Tel.: +7 (4912) 911-240
Fax.: +7 (4912) 911-232
techno@zil.tn.ru
4. —
5. AVCP 1 (1+3)
6. Harmonised standard: EN 13162:2012+A1:2015
Notified body No. 1023. Institut pro testování a certifikaci, a.s. třída Tomáše Bati 299, Louky, 763 02 Zlín Česká republika/Czech Republic tel/phone: +420 577601541
7. Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
Declared thermal conductivity at 10 °C, W/m*K	0,035	EN 13162:2012 + A1:2015
Limit deviations Length, Width, mm	±2/±1,5 %	
Limit deviations of thickness, mm	T4	
Thickness, (with increments of 10 mm), mm	50-200	
Deviation from squareness, mm/m	< 5	
Deviation from flatness, mm	< 6	
Compressive stress at 10% deformation, kPa	CS(10)10	
Tensile strength perpendicular to faces, kPa	TR5	
Point Load, N	PL(5)100	
Dimensional stability, %: -at specified temperature -under specified temperature (23°C) and humidity conditions (90%R.H.)	DS(70,-) <1 DS(23,90) <1	
Reaction to fire, euroclass	A1	
Water Absorption during Short/ Longterm Immersion kg/m2	WS <1 WL(P)<3	
Water vapour transmission, MU	MU1	
Dangerous Substances:	Does not include dangerous substances	

Declared Thermal resistance, EN 12667

Thickness,mm	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200
R. m ² *K/W	0,80	1,10	1,40	1,70	1,95	2,25	2,55	2,80	3,10	3,40	3,70	3,95	4,25	4,50	4,80	5,10	5,40	5,70

8. Appropriate Technical Documentation and/or Specific Technical Documentation: -

Signed for and on behalf of the manufacturer by:

Executive Director

«Zavod TECHNO» Ltd...At Ryazan on 24.09.18.



Kushnerevich Y.M.