

**DECLARATION OF PERFORMANCES**

No TNI/OEM/TP/2021\_05

- |  |  |
|--|--|
| 1. Unique identification code of the product type:<br>TNI/OEM/TP/2021_05<br>2. Intended use or uses:<br>Thermal insulation for buildings<br>3. Manufacturer: Technicol-Insulation Sp. z o.o.<br>ul. Wyzwolenia 55, 59-730 Nowogrodzic, Wykroty, Poland | 4. System or systems of assessment and verification of constancy of performance: AVCP 1 and 3<br>5. Harmonised standard: EN 13162:2012+A1:2015<br>6. Notified certification body or bodies:<br>Nr 1454 Instytut Mechanizacji Budownictwa i Górnictwa Skalnego<br>7. Declared performances: Table 1 |
|--|--|

Table 1

DECLARED PERFORMANCES				
Essential characteristics	Requirement clauses in the European standard	Symbol	Unit	Declared level and/or classes / NPD <sup>1)</sup>
Thermal Resistance	Thermal conductivity	$\lambda_D$	W/mK	0,036
	Thermal resistance	$R_D$	m <sup>2</sup> K/W	Table 2
	Thickness	Class of tolerance	mm	T5
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance	$R_D$	m <sup>2</sup> K/W	Table 2
	Thermal conductivity	$\lambda_D$	W/mK	0,036
	Dimensional stability under specified temperature	DS (70,-)	%	NPD
	Dimensional stability under specified temperature and humidity condition	DS (70,90)	%	≤1
Reaction to fire	Reaction to fire Euroclass characteristics	RtF	Euroclass	A1
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics	RtF	Euroclass	A1
Water permeability	Short time water absorption	WS	kg/m <sup>2</sup>	≤1
	Long time water absorption	WL(P)	kg/m <sup>2</sup>	≤3
Water vapour permeability	Water vapour transition	MU	-	1
Compressive strength	Compressive stress or compressive strength	CS(10)	kPa	NPD
	Point load	PL(5)	N	NPD
Tensile strength	Tensile strength perpendicular to the faces	TR	kPa	NPD
Durability of compressive strength against ageing/degradation	Compressive creep	CC(i1/i2/y)α <sub>c</sub>	mm	NPD
Impact noise transition index	Dynamic stiffness	$d_N$	mm	NPD
		SD	MN/m <sup>3</sup>	NPD
	Thickness	$d_L$	Mm	NPD
	Compressibility	C	mm	NPD
		Air flow resistivity	$d_N$	mm
Direct airborne sound insulation index	Air flow resistivity	A <sub>Fr</sub>	kPa·s/m <sup>2</sup>	NPD
		$d_N$	mm	NPD
Sound absorption index	Sound absorption	A <sub>p</sub> , A <sub>w</sub>	-	NPD
		-	-	NPD
Continuous glowing combustion	Continuous glowing combustion	-	-	NPD
Release of dangerous substances to the indoor	Release of dangerous substances	-	-	NPD

<sup>1)</sup> No Performance Declared

DECLARED THERMAL RESISTANCE															
Grubość [mm]	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160
$R_D$ [m <sup>2</sup> K/W]	-	-	-	1,35	1,65	1,90	2,20	2,50	2,75	3,05	3,30	3,60	3,85	4,15	4,40
Grubość [mm]	170	180	190	200	210	220	230	240	250	260	270	280	290	300	-
$R_D$ [m <sup>2</sup> K/W]	4,70	5,00	5,25	5,55	-	-	-	-	-	-	-	-	-	-	-

The performance of the product identified above is consistent with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:  
Piotr Bonarski  
Plant director  
Technicol-Insulation Sp. z o.o.  
ul. Wyzwolenia 55  
59-730 Nowogrodzic, Wykroty

Technicol Insulation Sp. z o.o.

  
 Piotr Bonarski  
Dyrektor Zakładu

..... Wykroty, 31.05.2021

**Technicol-Insulation Sp. z o. o.**  
ul. Młyńska 3A  
59-730 Nowogrodzic  
NIP: 6121867729 REGON: 383112788