

**DECLARATION OF PERFORMANCE**
No. XPS/011/CE/2020**1. Unique identification code of the product-type:****TECHNONICOL CARBON ECO**

d= 10, 20, 30, 40, 50, 60, 80, 100 mm

"F" (facade) - the presence of coarse surface on both sides of the board;

"D" (drainage) - in the presence of drainage channels on the surface of one side board;

Symbol plates supplemented with the words " SLOPE " with the designation of an appropriate slope in%

2. Intended use/es:

Extruded polystyrene boards TECHNOMICOL CARBON ECO are used in industrial, civil and transport engineering as thermal-insulation of building constructions in the temperature range -70 - +75°C

3. Manufacturer:FLLC "Roofing plant TechnoNIKOL",
Chapaeva, 11, Osipovichi 213760,
Republic of Belarus
Tel: +375 2235 61000**4. Authorised representative:****5. System/s of AVCP:**

System 3

6a. Harmonised standard:

EN 13164:2012 + A1:2015

Notified body/ies:№ 1023. Institute of tests and certification, PLC
Institut pro testování a certifikaci, a.s.
třída Tomáše Bati 299, Louky
763 02 Zlín
Česká republika/Czech Republic
Tel.: + 420 577601541

7. Declared performance:

F-XPS-EN 13164-T1-CS(10)200-DS(TH)-WL(T)0,7-WD(V)3

	Essential characteristics	Test method	Unit of measurement	Properties	Harmonized technical specification
1	Thermal conductivity, λ_D	EN 12667	W/m ² K	0,035	EN 13164:2012 + A1:2015
2	Thermal resistance, R_D	EN 12667	m ² *K/W	10 mm-0,285 20 mm-0,571 30 mm-0,857 40 mm-1,142 50 mm-1,428 60 mm-1,714 80 mm-2,285 100 mm-2,857	
3	Thickness, class T1	EN 823	mm	10, 20, 30, 40, 50, 60, 80, 100	
4	Width	EN 822	mm	580, 600	
5	Length	EN 822	mm	1180, 1200, 1250, 2380, 4000	
6	Reaction to fire, Euroclass	EN 13501-1	-----	Class F	
7	Compressive stress under 10% deformation, CS(10)	EN 826	kPa	≥ 200	
8	Long term water absorption by immersion, WL(T)	EN 12087	%	≤ 0.7	
9	Long term water absorption by diffusion, WD(V)	EN12088	%	≤ 3.0	
10	Dimensional stability, DS(TH)	EN 1604	%	Relative change of length, width and thickness not exceeding 5%	

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Edemsky O.Y.

Production director, FLLC "Roofing plant TechnoNIKOL"

Osipovichi, 20.01.2020

