


**DECLARATION OF PERFORMANCE**

No. MW/018R/CE/2021\_05

1. **TECHNOFLOOR STANDARD.** MW-EN 13162-T4- DS(70,-) DS(23,90)-CS(10)25- PL(5)50-WS-WL(P)-MU1 RtF:A1
2. Intended use: Thermal insulation boards for building
3. Manufacturer:  
 Limited Liability Company "Heat-Insulating Plant "TECHNO"  
 Having its seat in: LLC "Zavod TECHNO", Ryazan, Vostochnij Promuzel, building 21/58  
 ORIGIN: Russian Federation  
 Tel.: +7 (4912) 911-240  
 Fax.: +7 (4912) 911-232  
[techno@zil.tn.ru](mailto:techno@zil.tn.ru)
4. –
5. AVCP 1 and 3
6. Harmonised standard: EN 13162:2012+A1:2015  
 Notified body No. 1023. Institut pro testování a certifikaci, a.s. třída Tomáše Bati 299, Louky, 763 02 Zlín Česká republika/Czech Republic tel/phone: +420 577601541
7. Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
Declared thermal conductivity at 10 °C, $\lambda_D$ , W/m <sup>2</sup> K	0,037	EN 13162:2012 + A1:2015
Limit deviations Length, Width, mm	±2/±1,5 %	
Thickness, (with increments of 10 mm), mm	40-200	
Limit deviations of thickness, mm	T4	
Deviation from squareness, mm/m	< 5	
Deviation from flatness, mm	< 6	
Compressive stress at 10% deformation, kPa	CS(10) 25	
Point Load, N	PL(5)50	
Dimensional stability, %: -at specified temperature -under specified temperature (23°C) and humidity conditions (90%R.H.)	DS(70,-) <1 DS(23,90) <1	
Reaction to fire, euroclass	A1	
Water Absorption during Short/ Longterm Immersion kg/m <sup>2</sup>	WS <1 WL(P)<3	
Dynamic stiffness for 40 mm, MN/m <sup>3</sup>	23,7	
Water vapour transmission, MU	MU1	
Dangerous Substances:	Does not include dangerous substances	

Declared Thermal resistance, EN 12667

Thickness, mm	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200
R. m <sup>2</sup> *K/W	1,05	1,35	1,60	1,85	2,15	2,40	2,70	2,95	3,20	3,50	3,75	4,05	4,30	4,55	4,85	5,10	5,40

8. Appropriate Technical Documentation and/or Specific Technical

Signed for and on behalf of the manufacturer by:

Production Director

«Zavod TECHNO» Ltd...At Ryazan on 18.05.2021.

Goryachev V.V.

