



## DECLARATION OF PERFORMANCE No. 5.01

- |   |   |
|---|---|
| <b>1. Unique identification code of the product type:</b> | PIR boards F/F TECHNOMICOL  |
| <b>2. Intended use/es:</b>                                | Thermal insulation for buildings  |
| <b>3. Manufacturer:</b>                                   | Zavod Logicroof PIR LLC<br>Vostochny Promuzel 21, Ryazan, 390047, Russian Federation  |
| <b>4. System/s of AVCP:</b>                               | System 3  |
| <b>5. Harmonised standard:<br/>Notified body/ies:</b>     | EN 13165+A1:2016<br>1688 (Vilnius Gediminas Technical University, Faculty of Civil Engineering, Institute of Building Materials, Laboratory of Thermal Insulating Materials and Acoustics. Linkmenu 28, 08217 Vilnius). Test report # 1688-CPR-1864<br>1023 (INSTITUTE FOR TESTING AND CERTIFICATION, a.s. trida Tomase Bati 299, Louky, 763 02 Zlin, Czech Republic) |

### 6. Declared performance

Essential characteristics		Performance	
Thermal resistance	Thermal conductivity $\lambda_D$ (W/(m.K))	<b>0.022</b>	
	Thermal resistance $R_D$ ( $m^2.K/W$ )	$d_N$ 30mm	1.35
		$d_N$ 40mm	1.80
		$d_N$ 50mm	2.25
		$d_N$ 60mm	2.70
		$d_N$ 70mm	3.15
		$d_N$ 80mm	3.60
		$d_N$ 90mm	4.05
		$d_N$ 100mm	4.50
		$d_N$ 110mm	5.0
		$d_N$ 120mm	5.45
		$d_N$ 130mm	5.9
		$d_N$ 140mm	6.35
$d_N$ 150mm	6.81		
Durability of thermal resistance against of heat, weathering, ageing / degradation	Thermal conductivity $\lambda_D$ (W/(m.K))	<b>0.022</b>	
	Thermal resistance $R_D$ ( $m^2.K/W$ )	$d_N$ 30mm	1.35
		$d_N$ 40mm	1.80
		$d_N$ 50mm	2.25
		$d_N$ 60mm	2.70
		$d_N$ 70mm	3.15
		$d_N$ 80mm	3.60
		$d_N$ 90mm	4.05

		<b>d<sub>N</sub> 100mm</b>	<b>4.50</b>
		<b>d<sub>N</sub> 110mm</b>	<b>5.0</b>
		<b>d<sub>N</sub> 120mm</b>	<b>5.45</b>
		<b>d<sub>N</sub> 130mm</b>	<b>5.9</b>
		<b>d<sub>N</sub> 140mm</b>	<b>6.35</b>
		<b>d<sub>N</sub> 150mm</b>	<b>6.81</b>
	Thickness tolerance	<b>T2</b>	
Reaction to fire		<b>Class E</b>	
Durability of reaction to fire against heat, weathering, ageing / degradation		<b>Reaction to fire does not change with time</b>	
Dimensional stability under specified	48 h, 70 °C, 90 % R.H	<b>NPD</b>	
Temperature and humidity condition			
Deformation under specified compressive load and temperature conditions	40 kPa, 70°C, 168h	<b>NPD</b>	
Compressive strength	Compressive stress or compressive strength	<b>CS(10\Y)150 ≥ 150</b>	
Tensile / Flexural strength	Tensile strength perpendicular to faces	<b>NPD</b>	
Durability of compressive strength against ageing / degradation	Compressive creep	<b>NPD</b>	
Water permeability	Short term water absorption	<b>WS(P)0.1</b>	
	Flatness after one sided wetting	<b>FW2 ≤5</b>	
Water vapour permeability	Water vapor transmission	<b>NPD</b>	
Acoustic absorption index	Sound absorption	<b>NPD</b>	
Release of dangerous substances to the indoor environment	Release of dangerous substances	<b>No harmonized test method available</b>	
Continuous glowing combustion	Continuous glowing combustion	<b>No harmonized test method available</b>	

NPD: No Performance Determined



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Declaration is available on site:

[http://en.technicol.eu/materials/pir-thermal-insulation/logicpir\\_alu](http://en.technicol.eu/materials/pir-thermal-insulation/logicpir_alu)

Signed for and on behalf of the manufacturer by:

**Anton Taritcyn**

Product development & certification specialist  
Ryazan, December 7, 2018