



## DECLARATION OF PERFORMANCE No. 5.03

- |   |   |
|---|---|
| <b>1. Unique identification code of the product type:</b> | PIR boards GTM/GTB  |
| <b>2. Intended use/es:</b>                                | Thermal insulation for buildings  |
| <b>3. Manufacturer:</b>                                   | Zavod Logicroof PIR LLC<br>Vostochny Promuzel 21, Ryazan, 390047, Russian Federation  |
| <b>4. System/s of AVCP:</b>                               | System 3  |
| <b>5. Harmonised standard:<br/>Notified body/ies:</b>     | EN 13165+A1:2016<br>1023 (INSTITUTE FOR TESTING AND CERTIFICATION, a.s. trida Tomase Bati 299, Louky, 763 02 Zlin, Czech Republic)<br>1390 (Centrum stavebního inženýrství (CSI), a.s / Institute for testing and certification, a.s CSI division - Centrum stavebního inženýrství Prague, Accredited laboratory No.1007.4) |

### 6. Declared performance

Essential characteristics		Performance	
		d <sub>N</sub> 30mm	1.15
		d <sub>N</sub> 40mm	1.54
		d <sub>N</sub> 50mm	1.92
		d <sub>N</sub> 60mm	2.31
		d <sub>N</sub> 70mm	2.69
		d <sub>N</sub> 80mm	3.08
		d <sub>N</sub> 90mm	3.46
		d <sub>N</sub> 100mm	3.85
		d <sub>N</sub> 110mm	4.23
		d <sub>N</sub> 120mm	4.61
		d <sub>N</sub> 130mm	5.0
		d <sub>N</sub> 140mm	5.38
		d <sub>N</sub> 150mm	5.77
	Thermal conductivity λ <sub>D</sub> (W/(m.K))	0.026	
	Thickness tolerance	T2	
Reaction to fire		Class F	
Durability of reaction to fire against heat, weathering, ageing / degradation		Reaction to fire does not change with time	
Dimensional stability under specified temperature and humidity condition	48 h, 70 °C, 90 % R.H	NPD	

Deformation under specified compressive load and temperature conditions	40 kPa, 70°C, 168h	<b>NPD</b>
Compressive strength	Compressive stress or compressive strength	<b>CS(10\Y)150 ≥ 150</b>
Tensile / Flexural strength	Tensile strength perpendicular to faces	<b>NPD</b>
Durability of compressive strength against ageing / degradation	Compressive creep	<b>NPD</b>
Water permeability	Long term water absorption	<b>WL(T) ≤ 1.0</b>
	Flatness after one sided wetting	<b>FW2 ≤ 10</b>
Water vapour permeability	Water vapour transmission	<b>NPD</b>
Acoustic absorption index	Sound absorption	<b>NPD</b>
Release of dangerous substances to the indoor environment	Release of dangerous substances	<b>No harmonized test method available</b>
Continuous glowing combustion	Continuous glowing combustion	<b>No harmonized test method available</b>

NPD: No Performance Determined



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Declaration is available on site:

[http://en.technicol.eu/materials/pir-thermal-insulation/logicpir\\_gtb](http://en.technicol.eu/materials/pir-thermal-insulation/logicpir_gtb)

Signed for and on behalf of the manufacturer by:

**Anton Taritcyn**

Product development & certification specialist  
Ryazan, November 21, 2019