



# TECHNONICOL 70 PROFESSIONAL professional sealing foam

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 2/2/2017

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixtures  
Trade name : TECHNONICOL 70 PROFESSIONAL professional sealing foam  
Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only  
Use of the substance/mixture : Sealing, heat and noise-isolation joints, cracks, spaces, and assembly of parts in building and finishing works  
Function or use category : Insulating agents

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

UAB "Mida LT"  
Gamyklos g. 19  
LT 96155 Gargždai - Lietuva  
T +370 46 247021 - F +370 46 455167  
[zivile.paulauskaite@mida.lt](mailto:zivile.paulauskaite@mida.lt)

#### 1.4. Emergency telephone number

No additional information available

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Sensitisation — Respiratory, Category 1	H334
Sensitisation — Skin, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Extremely flammable aerosol. Causes skin and eye irritation. May cause an allergic skin reaction. Harmful by inhalation. May cause sensitization by inhalation. May cause cancer. Causes damage to organs (respiratory system) (inhalation).

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger  
Hazardous ingredients : 4,4'-methylenediphenyl diisocyanate  
Hazard statements (CLP) : H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation

# TECHNONICOL 70 PROFESSIONAL professional sealing foam

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H332 - Harmful if inhaled  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H335 - May cause respiratory irritation  
H351 - Suspected of causing cancer  
H373 - May cause damage to organs (Respiratory tract) through prolonged or repeated exposure (if inhaled)

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P211 - Do not spray on an open flame or other ignition source  
P251 - Do not pierce or burn, even after use  
P260 - Do not breathe vapours, spray  
P271 - Use only outdoors or in a well-ventilated area  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### 2.3. Other hazards

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated.

This mixture does not meet the PBT criteria of REACH regulation, annex XIII

This mixture does not meet the vPvB criteria of REACH regulation, annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
4,4'-methylenediphenyl diisocyanate	(CAS No) 101-68-8 (EC No) 202-966-0 (EC Index No) 615-005-00-9	30 - 50	Carc. 2, H351 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317
Propane	(CAS No) 74-98-6 (EC No) 200-827-9 (EC Index No) 601-003-00-5	5 - 20	Flam. Gas 1, H220 Press. Gas
Butane	(CAS No) 106-97-8 (EC No) 203-448-7 (EC Index No) 601-004-00-0	5 - 20	Flam. Gas 1, H220 Press. Gas
Dimethyl ether	(CAS No) 115-10-6 (EC No) 204-065-8 (EC Index No) 603-019-00-8	1 - 20	Flam. Gas 1, H220 Press. Gas

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
4,4'-methylenediphenyl diisocyanate	(CAS No) 101-68-8 (EC No) 202-966-0 (EC Index No) 615-005-00-9	(C >= 0.1) Resp. Sens. 1, H334 (C >= 5) STOT SE 3, H335 (C >= 5) Skin Irrit. 2, H315 (C >= 5) Eye Irrit. 2, H319

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Get medical attention immediately. Suspected of causing cancer.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Direct contact with the eyes is likely to be irritating. Consult an eye specialist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

# TECHNONICOL 70 PROFESSIONAL professional sealing foam

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. Inhalation may cause irritation (cough, short breathing, difficulty in breathing). Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Can cause pain and redness of the mouth and throat.
Chronic symptoms	: May cause cancer.

### 4.3. Indication of any immediate medical attention and special treatment needed

Irritation of the respiratory tract. May cause sensitisation by inhalation and skin contact. Treat symptomatically. Following severe exposure the patient should be kept under medical review for at least 48 hours.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Sand. Water spray may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Hazardous decomposition products in case of fire	: Carbon oxides (CO and CO <sub>2</sub> ). Nitrogen oxides. Hydrocarbons. Isocyanates. Hydrogen cyanide.

### 5.3. Advice for firefighters

Precautionary measures fire	: Keep container tightly closed and away from heat, sparks and flame.
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Exercise caution when fighting any chemical fire. Do not breathe fumes from fires or vapours from decomposition. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Normal equipment for firefighters i.e. fire kit (EN 469), gloves (EN 659) and boots (HO specification A29 and A30) in combination with breathing apparatus (EN 137).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ensure adequate ventilation, especially in confined areas. No open flames. No smoking. Remove ignition sources. Use special care to avoid static electric charges.
------------------	--

#### 6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

#### 6.1.2. For emergency responders

Protective equipment	: Avoid breathing Vapours. Use personal protective equipment as required. See Sections 8.
Emergency procedures	: Ensure adequate ventilation.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Stop leak without risks if possible.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. No open flames. No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, spray. Obtain special instructions before use. Do not handle

# TECHNONICOL 70 PROFESSIONAL professional sealing foam

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hygiene measures : until all safety precautions have been read and understood.  
: Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.  
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.  
Storage temperature : 5 - 25 °C  
Storage area : Store away from heat. Store in a well-ventilated place. Store locked up.  
Special rules on packaging : Keep only in original container. Store in a closed container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Dimethyl ether (115-10-6)		
EU	Local name	Dimethylether
EU	IOELV TWA (mg/m <sup>3</sup> )	1920 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	1000 ppm
Propane (74-98-6)		
EU	Local name	Propan
EU	IOELV TWA (mg/m <sup>3</sup> )	1800
EU	IOELV TWA (ppm)	1000 ppm
Butane (106-97-8)		
EU	Local name	Butan
EU	IOELV TWA (ppm)	600 ppm
EU	IOELV STEL (ppm)	750 ppm
Monitoring methods		
Monitoring methods	Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents	

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station. Do not breathe vapour/aerosol.

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Materials for protective clothing:

Antistatic clothing

#### Hand protection:

Protective gloves

#### Eye protection:

Chemical goggles or safety glasses

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection



# TECHNONICOL 70 PROFESSIONAL professional sealing foam

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Thermal hazard protection:

Keep away from open flames, hot surfaces and sources of ignition.

### Environmental exposure controls:

Avoid release to the environment. Do not exceed the occupational exposure limits (OEL).

### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Colourless.
Odour	: Earthy, musty.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: <= 30 kg/m <sup>3</sup> Testing method: GOST 409-77
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

Heat conductivity : 0,03 W/m.K (Method: GOST 7076-99)

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Thermal decomposition may produce : Carbon oxides (CO and CO<sub>2</sub>). Nitrogen oxides. Hydrocarbons. Isocyanates. Hydrogen cyanide.

# TECHNONICOL 70 PROFESSIONAL professional sealing foam

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust,mist: Harmful if inhaled.

ATE CLP (dust,mist)	3.000 mg/l/4h
---------------------	---------------

#### 4,4'-methylenediphenyl diisocyanate (101-68-8)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	9400 mg/kg
LC50 inhalation rat (mg/l)	≤ 0.559 g/m <sup>3</sup>
LC50 inhalation rat (Dust/Mist - mg/l/4h)	0.49 mg/l/4h

#### Dimethyl ether (115-10-6)

LC50 inhalation rat (ppm)	164000 ppm/4h
---------------------------	---------------

#### Propane (74-98-6)

LC50 inhalation rat (ppm)	> 800000 15min
---------------------------	----------------

#### Butane (106-97-8)

LC50 inhalation rat (mg/l)	1442 mg/l
----------------------------	-----------

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs (Respiratory tract) through prolonged or repeated exposure (if inhaled).
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

#### TECHNONICOL 70 PROFESSIONAL professional sealing foam

Vaporizer	Aerosol
-----------	---------

Potential adverse human health effects and symptoms : Harmful if inhaled.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Based on available data, the classification criteria are not met.

#### 4,4'-methylenediphenyl diisocyanate (101-68-8)

LC50 fish 1	1 g/l
EC50 Daphnia 1	129.7 (129.7 - 1000) mg/l
EC50 72h algae (1)	1640 mg/l
NOEC (chronic)	10 mg/l

#### Dimethyl ether (115-10-6)

LC50 fish 1	4.1 g/l
EC50 Daphnia 1	4.4 g/l
EC50 72h algae (1)	155 mg/l
NOEC (acute)	410 mg/l

#### Butane (106-97-8)

LC50 fish 1	24.11 (24.11 - 147.54) mg/l
EC50 Daphnia 1	14.22 (14.22 - 69.43) mg/l
EC50 72h algae (1)	7.71 (7.71 - 19.37) mg/l

#### 12.2. Persistence and degradability

#### TECHNONICOL 70 PROFESSIONAL professional sealing foam

Persistence and degradability	Not established.
-------------------------------	------------------

#### 4,4'-methylenediphenyl diisocyanate (101-68-8)

Persistence and degradability	The product is not biodegradable.
-------------------------------	-----------------------------------

#### Dimethyl ether (115-10-6)

Persistence and degradability	The product is not biodegradable.
-------------------------------	-----------------------------------

# TECHNICOL 70 PROFESSIONAL professional sealing foam

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Propane (74-98-6)	
Persistence and degradability	Readily biodegradable. Rapidly oxidizes at the air by photochemical reactions.

Butane (106-97-8)	
Persistence and degradability	Readily biodegradable.

### 12.3. Bioaccumulative potential

TECHNICOL 70 PROFESSIONAL professional sealing foam	
Bioaccumulative potential	Not established.

4,4'-methylenediphenyl diisocyanate (101-68-8)	
Log Pow	4.51

Dimethyl ether (115-10-6)	
Log Pow	0.07 @ 25 °C and pH 7

Butane (106-97-8)	
Log Pow	1.09 - 2.8 @ 20 °C and pH 7

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

TECHNICOL 70 PROFESSIONAL professional sealing foam	
This mixture does not meet the PBT criteria of REACH regulation, annex XIII	

This mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
--	--

Component	
4,4'-methylenediphenyl diisocyanate (101-68-8)	This substance does not meet the PBT criteria of REACH regulation, annex XIII This substance does not meet the vPvB criteria of REACH regulation, annex XIII
Dimethyl ether (115-10-6)	This substance does not meet the PBT criteria of REACH regulation, annex XIII This substance does not meet the vPvB criteria of REACH regulation, annex XIII
Propane (74-98-6)	This substance does not meet the PBT criteria of REACH regulation, annex XIII This substance does not meet the vPvB criteria of REACH regulation, annex XIII
Butane (106-97-8)	This substance does not meet the PBT criteria of REACH regulation, annex XIII This substance does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

Additional information : Avoid release to the environment

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Dispose in accordance with corresponding regulations. Disposal of defect or damaged product is performed in accordance with instruction from manufacturer or in accordance with local regulation. Disposal may be performed only by the authorized person. For the classification of waste and its removal corresponding to the waste producer.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.
Additional information	: Flammable vapours may accumulate in the container. Hazardous waste due to potential risk of explosion.
Ecology - waste materials	: Avoid release to the environment. Do not dispose of waste into sewer.
European List of Waste (LoW) code	: 15 01 10* - packaging containing residues of or contaminated by dangerous substances (*Hazardous waste)
HP Code	: HP3 - "Flammable:" — other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP4 - "Irritant — skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP7 - "Carcinogenic:" waste which induces cancer or increases its incidence HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.

## SECTION 14: Transport information

In accordance with ADN / ADR / IATA / IMDG / RID

# TECHNONICOL 70 PROFESSIONAL professional sealing foam

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 14.1. UN number

UN-No. (ADR)	: 1950
UN-No. (IMDG)	: 1950
UN-No. (IATA)	: 1950
UN-No. (ADN)	: 1950
UN-No. (RID)	: 1950

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: AEROSOLS
Proper Shipping Name (IMDG)	: AEROSOLS
Proper Shipping Name (IATA)	: Aerosols, flammable
Proper Shipping Name (ADN)	: AEROSOLS
Proper Shipping Name (RID)	: AEROSOLS
Transport document description (ADR)	: UN 1950 AEROSOLS (Dimethyl ether, Propane, Butane), 2.1, (D)
Transport document description (IMDG)	: UN 1950 AEROSOLS (Dimethyl ether, Propane, Butane), 2.1
Transport document description (IATA)	: UN 1950 Aerosols, flammable (Dimethyl ether, Propane, Butane), 2.1
Transport document description (ADN)	: UN 1950 AEROSOLS (Dimethyl ether, Propane, Butane), 2.1
Transport document description (RID)	: UN 1950 AEROSOLS (Dimethyl ether, Propane, Butane), 2.1

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR)	: 2.1
Danger labels (ADR)	: 2.1



#### IMDG

Transport hazard class(es) (IMDG)	: 2.1
Danger labels (IMDG)	: 2.1



#### IATA

Transport hazard class(es) (IATA)	: 2.1
Hazard labels (IATA)	: 2.1



#### ADN

Transport hazard class(es) (ADN)	: 2.1
Danger labels (ADN)	: 2.1



#### RID

Transport hazard class(es) (RID)	: 2.1
Danger labels (RID)	: 2.1



# TECHNONICOL 70 PROFESSIONAL professional sealing foam

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



### 14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP02
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

#### - Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP02
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

#### - Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

#### - Inland waterway transport

Classification code (ADN)	: 5F
---------------------------	------

# TECHNONICOL 70 PROFESSIONAL professional sealing foam

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

### - Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP02
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP)  
Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers as amended (2013/10/EU a 2016/2037/EU)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
BCF	Bioconcentration factor
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
DPD	Dangerous Preparations Directive 1999/45/EC
DSD	Dangerous Substances Directive 67/548/EEC
EC50	Median effective concentration
IATA	International Air Transport Association
IOELV	Indicative occupational exposure limit values
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

# TECHNONICOL 70 PROFESSIONAL professional sealing foam

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
TLM	Median Tolerance Limit
TWA	Time-weighted average
vPvB	Very Persistent and Very Bioaccumulative
VOC	Volatile organic compounds

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Dissemination portal ECHA <https://echa.europa.eu/cs/search-for-chemicals>

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging. Provide SDS to employees. Follow general rules on handling chemical substances and/or mixtures. Safety training for chemicals handling.

Other information : None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Press. Gas	Gases under pressure
Resp. Sens. 1	Sensitisation — Respiratory, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H229	Pressurised container: May burst if heated
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Aerosol 1	H222;H229	On basis of test data
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*